

EM-3011A

Fingerprint Module

Small size capacitive module



With proven fingerprint capture technology, the ARATEK EM-3011A Fingerprint Module is compliant with international standard including ISO and ANSI support. It is applicable for authentication in different industries such as Time & Attendance finance, health care, hospitality etc.

Features

- **International Standard**
ISO19794-2, ISO19794-4, ANSI 378, ANSI 381 and WSQ supported
- **High Image Quality**
Capacitive fingerprint technology with superior image quality
- **Strong Adaption**
Good adaption for dry, moist and rough fingerprints
- **Correction and Authentication**
Support auto correction and 360 degree rotation authentication
- **Cloud Platform**
Seamlessly join in Aratek TrustLink™ biometrics authentication platform
- **OS Support**
Windows2000, XP, Vista, Windows 7 / 8 / 10, Android and other embedded systems
- **SDK**
Comprehensive software development kit is available for development and integration

Applications

- PC/Network Security
- Hospitality
- Finance and Banking
- Telecommunication
- Healthcare
- Law Enforcement

EM-3011A Fingerprint Module

Physical Parameter

Dimension	33*20*5mm (L*W*H)
-----------	-------------------

Performance Parameter

Capture Mode	Capacitive Touch
Platen Size	15.3*11.4 mm
Sensing Area	14.4*10.4 mm
Fingerprint Image Size	208*288 pixels
Image Resolution	508 dpi
Gray level	256 level

Communication Mode


Communication Interface	UART (TTL 115200bps default), USB1.1 / 2.0 SPI
-------------------------	--

Operation Environment

Work Voltage	3.8-5V
Work Current	50mA
Temperature	0°C~55°C
Humidity	20-90%R.H
ESD	Contact: ± 6KV Air: ± 8KV

Supported OS

Windows XP / 7 / 8 / 10, Android



Aratek Biometrics Technology Co., Ltd

10F, No. 131, Songjiang Road, Zhongshan District, Taipei City 10491, Taiwan
Tel : +886 2-2501-0001
E-mail : sales@aratek.co
Web : www.aratek.co